(12)

## **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 20.06.2001 Bulletin 2001/25

(51) Int Cl.7: G02F 1/1335

- (21) Application number: 00403497.1
- (22) Date of filing: 13.12.2000
- (84) Designated Contracting States:
  AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
  MC NL PT SE TR
  Designated Extension States:
  AL LT LV MK RO SI
- (30) Priority: 13.12.1999 JP 35321799
- (71) Applicant: SONY CORPORATION Tokyo (JP)

- (72) Inventors:
  - Tetsuo, Urabe, c/o Sony Corporation Shinagawa-ku, Tokyo (JP)
  - Nobuyuki, Shigeno, c/o Sony Corporation Shinagawa-ku, Tokyo (JP)
  - Takayuki, Fujioka, c/o Sony Corporation Shinagawa-ku, Tokyo (JP)
- (74) Representative: Thévenet, Jean-Bruno et al Cabinet Beau de Loménie 158, rue de l'Université 75340 Paris Cédex 07 (FR)
- (54) Display apparatus with colour filter and method of manufacturing the same
- (57) A hybrid type display apparatus capable of maintaining color purity in a case of transmission mode display, and improving lightness of color in a case of reflection mode display is provided. This hybrid type display apparatus is comprised of: a pair of first and second substrates (1,2); a first electrode (10) provided on an internal surface of the first substrate (1); a second electrode (11) provided on an internal surface of the second substrate (2); a color filter (CF) provided on the first sub-

strate (1), aligned with a pixel in a portion between the first electrode and the second electrode; a liquid crystal layer (3) interposed between the pair of substrates; and a reflection layer (8) provided on the second substrate. The reflection layer (8) has a hole provided for each pixel, which divides a plane of each pixel into a transmission portion (T) within the hole and a reflection portion (R) outside the hole. The color filter comprises a lamination of a colored layer (50) and a transparent layer (51).

## FIG. 1A

